EDW 402-II



Thyristorised Engine Driven Welding Generator



Compact Thyrsitorised EDW

EDW 402-II is a CPCB-II compliant heavy duty silenced welding generator for on site usage. The thyristorised rectifier block enables improved current regulation for stable output including very good performance with cellulosic electrodes. Multiple safety features ensures prolonged life with ease of maintenance features like indicators for oil pressure, fuel / lube oil level, engine speed, hour meter etc

- Compact design for improved mobility
- Fine controls –Normal, Cellulosic 2.5 / 3.15 modes
- Variable Arc force Control
- In-built hot start for improved arc initiation
- Protection from thermal overloading (welding) & overcurrent (auxiliary power)

Application Areas

- Construction & Erection projects.
- Cross Country Pipelines
- Mines
- Defences



Specifications / Technical data		EDW 402– II		
Engine				
Make , Model		Simpson, SJ327 TAA (G)		
Engine Rating (Hp) at speed (rpm)		38 at 1500		
No. Of Cylinders		3	3	
Aspirations		Turbo Charged	Turbo Charged	
Cooling		Water (Coolant)		
Starting		12V Elecrtic		
Battery, Ah		80		
Fuel Tank Capacity, Litres		Diesel, 64	Diesel , 64	
Fuel Consumption at Rated Current, Ltr / hr		4.2		
Welding Output				
Open Circuit Voltage, V		94		
Output Current Range, A		40 - 400		
Maximum Output/ % duty Cycle, A / %		400 / 60%		
Maximum Output/ % duty Cycle, A / %		310 / 100%		
Electrode Diameter, mm		2.5 - 6.3		
Insulation Class		Н		
Auxillary Power				
3 Phase supply (100% Duty Cycle): KVA x No of Outlets, V x Ph, Hz		7 x 1, 400 x 3 ,50		
1 Phase supply (100% Duty Cycle): KVA x No of Outlets, V x Ph, Hz		2.5 x 1, 220 x 1, 50		
Size				
Dimensions, lxbxh (without trailer), mm		2300 X 950 X 1200		
Weight, Kg		1100		
Under-Carriage with towbar		2 wheels + Leaf-Springs		
Noise Level		75dB at 1m(CPCB-II)		
Ordering Information				
Description	Part number	Description	Part number	
EDW 402-II	4610 202 405	Holder Confort 600	200 200 1002	
HFR Weld Cable Cu 50sq mm	4600 600 182	Eco Arc II Helmet (83x108mm)	0700 000 986	



Weld Cable AI 95sq mm HOFR

ESAB / esabindia.com

Regd & H. O. : ESAB INDIA LIMITED 13, Industrial Estate, III Main Road Ambattur, Chennai – 600058 Email: info@esab.co.in

4600 600 175

Note : EDW 402-II is delivered with 3m Remote control unit.



Welding Hand Gloves



2001 005 001